

The "Illusion" of Privacy

SWAN Expo 2022

Who Are We?



Rudy Host – SWAN Systems Engineer 13 Years in Library Technology, 6 with SWAN Secure System Design, Custom App Development



Ian Nosek – SWAN Systems Administrator 17 Years in Library Technology, 7 with SWAN ILS and System Administration, Third-Party Integrations

Magic Time



What is SIP2?

- SIP2 is the industry standard for library authentication and self-service applications
 - Self-checks
 - Computer reservation systems
 - Material handling systems

- Electronic Resources
- Research Databases
- SIP (Standard Interchange Protocol) was developed by 3M to transmit user data between selfcheck systems and an ILS (Integrated Library System)
- Developed by 3M and released in 1993, with Version 2 of the SIP standard published in 2006

```
2022-07-26 14:06:38,084, 13408, INFO , IlsConnector, requestPatronInformation, Requesting user information for 21140003533188

2022-07-26 14:06:38,085, 13408, INFO , IlsConnector, processSipRequest, Sending message on socket 2022-07-26 14:06:38,085, 13408, INFO , IlsConnector, processSipRequest, Sent message on socket 2022-07-26 14:06:38,085, 13408, INFO , IlsConnector, processSipRequest, Creating empty SipResponse 2022-07-26 14:06:38,086, 13408, INFO , IlsConnector, processSipRequest, Created empty SipResponse, checking if connected 2022-07-26 14:06:38,086, 13408, INFO , IlsConnector, processSipRequest, Checked if connected, getting reply from socket
```


What data does SIP2 carry?

- Transactional data between client and server
- Patron authentication returns most of the personally identifiable information (PII) saved in the patron's record, including:
 - Name
 - Home Address
 - Fmail Address
 - Birthdate

- Gender
- Barcode
- PIN

Ubiquitous but Flawed

- The SIP2 standard does not offer any native encryption
 - Encryption is a way to conceal information by altering it so that it appears to be random data.
- All data passed via SIP2 is delivered in plain-text



What is SWAN doing?

- SWAN is <u>no longer</u> configuring any external SIP2 connections unless they explicitly support TLS encryption
- Existing vendors will eventually be required to use an encrypted port
- We are currently working with Overdrive on TLS implementation, and anticipate having Overdrive secured later this year
- SIP2 is ubiquitous, but there are other authentication methods available
 - OpenAthens Proxy Supports basic barcode authentication and is used for the majority of research databases
 - Web Services A proprietary SirsiDynix API which serves as the connection method for Aspen, Communico, BLUEcloud, and others

Securing SIP2 Traffic

- While SIP2 traffic is unencrypted, SWAN is actively working to increase the security of all transmitted PII
- All SIP2 connections internal to the library (reservation systems, self-checks, etc.) are encrypted by way of the VPN tunnel that connects each library to SWAN
- Most external vendors (Overdrive, Hoopla, etc.) are not currently encrypted, but options are available to secure these connections
 - TLS-SIP2 encrypts transmitted data via Transport Layer Security (TLS)
 SirsiDynix supports TLS-SIP2 natively in our current version
 - Stunnel is an open-source application that is capable of securing connections that have no native encryption

What can you do?

- Consult with SWAN prior to selecting new vendors
 - Each vendor integration requires a unique configuration on our server
 - The sooner we're involved, the faster we can identify any challenges
- Ask potential vendors what authentication types they support
 - While most vendors will simply request a SIP2 connection, there may be other authentication methods that satisfy a vendor's requirements
- Principle of Least Access
 - Only the minimum necessary rights should be assigned to a subject that requests access to a resource and should be in effect for the shortest duration necessary (remember to relinquish privileges). Granting permissions to a user beyond the scope of the necessary rights of an action can allow that user to obtain or change information in unwanted ways. Therefore, careful delegation of access rights can limit attackers from damaging a system.

Magic revealed

```
payload_data = ByteStringToString(packet.tcp.payload)

barcode = re.search("\|AA(.+?)\|", payload_data)[1]
name = re.search("\|AE(.+?)\|", payload_data)[1]
address = re.search("\|BD(.+?)\|", payload_data)[1]
email = re.search("\|BE(.+?)\|", payload_data)[1]
birthdate = re.search("\|PD(.*?)\|", payload_data)[1]
formatted_birthdate = f'{birthdate[4:6]}/{birthdate[6:8]
os.system('clear')
print(f'I found a patron named {name}. Their barcode is
```

Raspberry Pi


 Small computer running Linux OS

VPN software Connection back to SWAN servers

Very small
Python
script

Intercepting and interpreting SIP2 traffic

Repeat Demo



Questions?

